

STYLISH AND INNOVATIVE
4 INCH RECEIPT / LABEL PORTABLE PRINTER



MOBILE PRINTER

LK-P41

- High gloss cover and 2 color LEDs
- IP42, IP54(with optional case) certified : protection against dust and water
- Adjustable paper width from 50mm to 112mm
- 2 types of battery selectable – 2200/4400mAh Li-ion
- Large capacity, paper rolls up to 56mm (OD)
- Highly reliable Bluetooth communications or Wi-Fi(802.11b/g) available(option).
- ESC/POS, CPCL command compatible
- Various O/S drivers : Win CE/Mobile, Symbian, Linux, Blackberry, Android





SPECIFICATION

ITEM	TYPE	
MODEL	LK-P41	
PRINTING	METHOD	Direct Thermal
	SPEED	80mm / sec
DOT DENSITY	203 DPI	
DOT PITCH	8dots /mm, 0.125 pitch	
EFFECTIVE PRINTING WIDTH	104mm, 832dots/line	
PAPER	TYPE	Thermal Paper / Label
	WIDTH	50mm ~ 112mm
	THICKNESS	0.06mm ~ 0.16mm
	ROLL DIAMETER	Max. ϕ 56.0mm
	ROLL CORE INNER	12.5mm \pm 0.5mm
RELIABILITY	TPH LIFE	50km
	PULSE ACTIVATION	50,000,000pulse or more
FONTS and GRAPHICS	STANDATD FONTS	Seven residnet fonts 12-48 pt.
	OPTIONAL	International character sets
	GRAPHICS, LINE AND BOX DRAWING	PCX and Bitmap
BARCODE	EAN-8, EAN-13, Code 39, ITF, UPC-A, UPC-E, Codabar, Code 93, Code 128, PDF 417(2D), QR Code(2D), Maxicode(2D)	
EMULATION	ESC/POS, CPCL Command compatible	
DRIVER	Window Printer Driver(7, XP, 2000, 2003, VISTA, 32 & 64bit), Windows (CE 4.2 & 5.0 / Mobbile 5.0), Linux Printer Driver Symbian, Blackberry, Android	
SENSOR	Paper end / Black mark / Gap / Cover open sensors	
INTERFACE	STANDARD	Serial(RS-232C), USB
	OPTION	Bluetooth class 2, Wi-Fi (802.11b/g)
BATTERY CHARGER	External Charger (Output 8.4VDC/0.8A)	
BATTERY	7.4V 2200mAh, 2600mAh, 5200mAh 3.7Hrs charging time, 20Hrs stand-by	
DIMENSION	149.2mm x 162mm x 70mm (W x D x H)	
WEIGHT	572g (With 2200mAh Battery)	
TEMPERATURE	OPERATION	-10 ~ 50°C
	STORAGE	-20 ~ 60°C
HUMIDITY	OPERATION	35 ~ 80%
	STORAGE	10 ~ 90%

COVER OPEN




ACCESSORIES



CASE

CRADLE

STRAP



SEWOO TECH Co., Ltd.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, Korea 447-210

T. +82-31-459-8200 F. +82-31-459-8880

026-91003374