

W-POS

The Core of Evolution



GOD DESIGN



Simple and refined design



Space-saving 3 inch Built-in Printer



Bright and clear wide screen display



Support hi-performance i3/i5/i7 CPU



User Convenient Front IC Card Reader



Adapted PCAP Multi Touch Screen

OKPOS™



The Core of Evolution W-POS

- World Best Touch POS System
- User Convenient Wide Touch Display



Wide Touch Display



Second Display Monitor



3 inch built-in Printer



Front IC Card Reader

Specification

	W-156	W-185
CPU	Intel® Celeron® Baytrail J1900 CPU onboard (Entry) Intel Core Cal/i3/i5/i7 (Skylake) LGA1151 64(32)bit (Hi-End)	Intel® Celeron® Baytrail J1900 CPU onboard (Entry) Intel Core Cal/i3/i5/i7 (Skylake) LGA1151 64(32)bit (Hi-End)
Memory	DDR4 SODIMM 2GB (up to 8GB, 1 slot) (Entry) DDR3 SODIMM 4GB (up to 8GB, 1 slot) (Hi-end)	DDR4 SODIMM 2GB (up to 8GB, 1 slot) (Entry) DDR3 SODIMM 4GB (up to 8GB, 1 slot) (Hi-end)
Storage	2.5" SATA-II 64GB SSD or 320GB HDD	2.5" SATA-II 64GB SSD Or 320GB HDD
LCD	15.6" TFT LCD (250cd), LVDS Interface	18.5" IPS LCD Pannel (250cd), LVDS Interface
Resolution	1366 x 768 (16:9)	1366 x 768 (16:9)
Touch	15.6" (Capacitive 10Point Multi Touch) USB interface	18.5" (Capacitive 10Point Multi Touch) USB interface
Indicator	2 x LED 1 x Buzzer	2 x LED 1 x Buzzer
Speaker	1 x 1W	1 x 1W
USB	6 x USB (Side: 4 x USB, Front: 2 x USB)	6 x USB (Side: 4 x USB, Front: 2 x USB)
Serial	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45) COM1/4: 0/5/12V by Jumper, COM2/3: 0/5/12V by BIOS select	4 x RS-232C (3 x Powered DSUB-9, 1 x RJ-45) COM1/4: 0/5/12V by Jumper, COM2/3: 0/5/12V by BIOS select
PS/2	1 x Keyboard or Mouse	1 x Keyboard or Mouse
LAN	1 x Gigabit LAN port	1 x Gigabit LAN port
VGA	1 x VGA port	1 x VGA port
Audio	1 ports (1 x Line-out)	1 ports (1 x Line-out)
DC-IN	External 60W Adapter(Entry) / 96W Adaptor(Hi-end) Input AC 100~240V/50~60Hz, Output DC 12V/5A	External 60W Adapter(Entry) / 96W Adaptor(Hi-end) Input AC 100~240V/50~60Hz, Output DC 12V/5A
Temperature	Operating 0°C to 60°C, Storage -20°C to 80°C	Operating 0°C to 60°C, Storage -20°C to 80°C
Dimension	406.5(W) X 319.6(H) X 310.3(D)	477.5(W) X 337(H) X 310.3(D)
Weight	9.3kg	10.4Kg
MSR	ISO 1,2,3, Tracks Reading	ISO 1,2,3, Tracks Reading
SCR	EMV level 1, 2	EMV level 1, 2
OS	Windows POSReady7, Windows 10 IoT Entry	Windows POSReady7, Windows 10 IoT Entry
2nd Display	9.7" TFT LCD (1024 x 768)	9.7" TFT LCD (1024 x 768)
CDP	VFD (20 columns x 2 lines)	VFD (20 columns x 2 lines)
Built-in Printer	3" Thermal Printer (24V/2.5A External)	3" Thermal Printer (24V/2.5A External)
Cash Drawer Port	Serial trigger	Serial trigger



OKPOS™

8F, Ace High-End Tower 6th, 234, Beotkkot-ro, Geumcheon-gu, Seoul, Korea (08513)
Tel +82 70 7425 9001 Fax +82 2 6299 5447 URL www.okposkorea.com



Call:026 - 91003374